

1. Identification

Product identifier	Pipe-Dri (4297-76)
Other means of identification	Not available.
Recommended use	Insulation
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	Nu-Calgon
Address	2611 Schuetz Road St. Louis, MO 63043 United States
Telephone	314-469-7000 / 800-554-5499
E-mail	Not available.
Emergency phone number	1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazard identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Liquefied gas
Health hazards	Serious eye damage/eye irritation	Category 2
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.	
Precautionary statement		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection.	
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.	
Storage	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of container in accordance with local, regional, national and international regulations.	
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known	
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60-80*

Chemical name	Common name and synonyms	CAS number	%
Octadecanoic acid		57-11-4	1-5*
Octadecanoic acid, zinc salt		557-05-1	1-5*
Petroleum gases, liquefied, sweetened		68476-86-8	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Ingestion	Not likely, due to the form of the product. Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not re-use empty containers. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure controls/Personal protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm
	TWA	1200 mg/m3 500 ppm
Octadecanoic acid (CAS 57-11-4)	TWA	10 mg/m3
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	10 mg/m3

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Octadecanoic acid (CAS 57-11-4)	TWA	10 mg/m3	
Octadecanoic acid, zinc salt (CAS 557-05-1)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3 10 mg/m3	Respirable fraction. Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Octadecanoic acid (CAS 57-11-4)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Octadecanoic acid (CAS 57-11-4)	TWA	3 mg/m3	Respirable fraction.
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	3 mg/m3	Respirable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
		1000 ppm
	TWA	1190 mg/m3
		500 ppm
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	10 mg/m3

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Acetone (CAS 67-64-1)	15 minute	750 ppm
	8 hour	500 ppm
Octadecanoic acid (CAS 57-11-4)	15 minute	20 mg/m3
	8 hour	10 mg/m3
Octadecanoic acid, zinc salt (CAS 557-05-1)	15 minute	20 mg/m3
	8 hour	10 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
Octadecanoic acid, zinc salt (CAS 557-05-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Octadecanoic acid (CAS 57-11-4)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm	
Octadecanoic acid, zinc salt (CAS 557-05-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first.

Other Wear appropriate chemical resistant clothing. As required by employer code.

Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and chemical properties

Appearance	Misty spray
Physical state	Gas.
Form	Aerosol.
Color	White
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	50 psig @ 20°C
Vapor density	Not available.
Relative density	0.726
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	25 cP @ 25°C
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix with other chemicals.
Incompatible materials	Acids.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
---------------------------	---

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	> 15800 mg/kg, Health Canada (HSA)
Inhalation		
LC50	Rat	76 mg/l/4h, Health Canada (HSA)
Oral		
LD50	Rat	5800 mg/kg, Health Canada (HSA)
Octadecanoic acid (CAS 57-11-4)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Rat	> 0.2 mg/L, 4 Hours, ECHA
Oral		
LD50	Rat	> 5000 mg/kg, ECHA
Octadecanoic acid, zinc salt (CAS 557-05-1)		
Acute		
Dermal		
LD50		
	Rat	2000 mg/kg
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	>= 5000 mg/kg
Petroleum gases, liquefied, sweetened (CAS 68476-86-8)		
Acute		
Dermal		
LD50	Not available	
Inhalation		
LC50	Rat	1442738 mg/m3, 10 Minutes, ECHA 1443 mg/L, 10 Minutes, ECHA
Oral		
LD50	Not available	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Octadecanoic acid (CAS 57-11-4) Irritant

Octadecanoic acid, zinc salt (CAS 557-05-1) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity See below.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components	Species		Test Results
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/L, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

UN number UN1950
Proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)
Hazard class Limited Quantity - US

Transportation of Dangerous Goods (TDG - Canada)**Basic shipping requirements:**


UN number UN1950
Proper shipping name AEROSOLS, flammable
Hazard class Limited Quantity - Canada
Packaging exceptions <1L - Limited Quantity

IATA/ICAO (Air)**Basic shipping requirements:**

UN number UN1950
Proper shipping name Aerosols, flammable
Hazard class Limited Quantity - IATA

IMDG (Marine Transport)**Basic shipping requirements:**

UN number UN1950
Proper shipping name AEROSOLS
Hazard class Limited Quantity - IMDG

DOT; IMDG; TDG**IATA**

15. Regulatory information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Octadecanoic acid, zinc salt (CAS 557-05-1)	Listed.
Petroleum gases, liquefied, sweetened (CAS 68476-86-8)	Listed.

Canada Priority Substances List (Second List): Listed substance

Octadecanoic acid, zinc salt (CAS 557-05-1)	Listed.
---	---------

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Acetone (CAS 67-64-1)	Class B
-----------------------	---------

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.
Octadecanoic acid, zinc salt (CAS 557-05-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Octadecanoic acid, zinc salt	557-05-1	1-5*

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below**US - California Hazardous Substances (Director's): Listed substance**

Acetone (CAS 67-64-1) Listed.
Octadecanoic acid, zinc salt (CAS 557-05-1) Listed.

US - Illinois Chemical Safety Act: Listed substance

Acetone (CAS 67-64-1)
Octadecanoic acid, zinc salt (CAS 557-05-1)

US - Louisiana Spill Reporting: Listed substance

Acetone (CAS 67-64-1) Listed.
Octadecanoic acid, zinc salt (CAS 557-05-1) Listed.

US - Michigan Critical Materials Register: Parameter number

Octadecanoic acid, zinc salt (CAS 557-05-1)

US - Minnesota Haz Subs: Listed substance

Acetone (CAS 67-64-1) Listed.
Octadecanoic acid (CAS 57-11-4) Listed.
Octadecanoic acid, zinc salt (CAS 557-05-1) Listed.

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Petroleum gases, liquefied, sweetened (CAS 68476-86-8)

US - Texas Effects Screening Levels: Listed substance

Acetone (CAS 67-64-1) Listed.
Octadecanoic acid (CAS 57-11-4) Listed.
Octadecanoic acid, zinc salt (CAS 557-05-1) Listed.
Petroleum gases, liquefied, sweetened (CAS 68476-86-8) Listed.

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Octadecanoic acid, zinc salt (CAS 557-05-1)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Octadecanoic acid, zinc salt (CAS 557-05-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Octadecanoic acid, zinc salt (CAS 557-05-1)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Octadecanoic acid, zinc salt (CAS 557-05-1)

US. California Proposition 65

WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

28-January-2021

Version #

02

Effective date

28-January-2021

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Further information

Not available.

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.